U.S. Ser. No. 10/092,320 Docket No. DP-306837

Amendment

## AMENDMENTS TO THE CLAIMS:

This listing of the pending claims will replace all prior versions and listings of claims in this application:

1. (Currently Amended) A powertrain mount comprising:

an upper orifice plate;

a lower orifice plate; and

a generally flat and planar diaphragm having an enlarged central node and a periphery spaced apart from the central node, the central node having a continuous curvature and being disposed generally entirely at a central portion of the diaphragm, wherein the central node is in constant contact with the upper orifice plate and in contact with the lower orifice plate, and wherein the periphery is spaced apart from at least one of the upper or lower orifice plates and free to move between the upper orifice plate and the lower orifice plate.

- 2. (Original) The powertrain mount of claim 1 wherein the upper orifice plate includes a plurality of holes through which fluid may flow.
- (Original) The powertrain mount of claim 2 wherein the holes have a generally circular cross-section.
- 4. (Original) The powertrain mount of claim 1 wherein the lower orifice plate includes a plurality of holes through which fluid may flow.
- (Original) The powertrain mount of claim 4 wherein the holes have a generally circular cross-section.
- (Original) The powertrain mount of claim 1 wherein the periphery of the diaphragm includes a raised rim.
- 7. (Original) The powertrain mount of claim 1 wherein the upper and lower orifice plates define

U.S. Ser. No. 10/092,320 Docket No. DP-306837 Amendment

an orifice track.

- 8. (Currently Amended) A powertrain mount comprising:
  - an upper orifice plate;
  - a lower orifice plate; and
- a generally flat and planar diaphragm including an enlarged <u>and substantially spherical</u> central node and a periphery spaced apart from the central node, the central node <u>having a continuous curvature and</u> being disposed generally entirely at a central portion of the diaphragm, wherein the central node is in constant contact with the upper orifice plate and in contact with the lower orifice plate, and wherein the periphery includes a raised rim that is spaced apart from at least one of the upper or lower orifice plates and free to move between the upper orifice plate and the lower orifice plate.
- (Original) The powertrain mount of claim 8 wherein the upper orifice plate includes a plurality of holes through which fluid may flow.
- 10. (Original) The powertrain mount of claim 9 wherein the holes have a generally circular cross-section.
- 11. (Original) The powertrain mount of claim 8 wherein the lower orifice plate includes a plurality of holes through which fluid may flow.
- 12. (Original) The powertrain mount of claim 11 wherein the holes have a generally circular cross-section.
- 13. (Original) The powertrain mount of claim 8 wherein the upper and lower orifice plates define an orifice track.
- 14. (Currently Amended) A powertrain mount comprising: an upper orifice plate having a plurality of holes through which fluid may flow;

U.S. Ser. No. 10/092,320 Docket No. DP-306837 Amendment

- a lower orifice plate having a plurality of holes through which fluid may flow; and a generally flat and planar diaphragm having an enlarged and substantially spherical central node and a periphery spaced apart from the central node, the central node having a continuous curvature and being disposed generally entirely at a central portion of the diaphragm, wherein the central node is in constant contact with the upper orifice plate and in contact with the lower orifice plate, and wherein the periphery is spaced apart from at least one of the upper or lower orifice plates and free to move between the upper orifice plate and the lower orifice plate.
- 15. (Original) The powertrain mount of claim 14 wherein the holes in the upper orifice plate have a generally circular cross-section.
- 16. (Original) The powertrain mount of claim 14 wherein the holes in the lower orifice plate have a generally circular cross-section.
- 17. (Original) The powertrain mount of claim 14 wherein the periphery of the diaphragm includes a raised rim.
- 18. (Original) The powertrain mount of claim 14 wherein the upper and lower orifice plates define an orifice track.
- 19. (New) The powertrain mount of claim 1 wherein the central node is substantially spherical in shape.